



# SILICONE SPRAY NL/FR/DE

UNIVERSAL TRANSPARENT SLIPPING, LUBRICATING AND ANTI-ADHESION AGENT



## APPLICATION

### Directions for use:

Shake well before use. Spray surface(s) evenly from a distance of approx. 10-20 cm.

**Points of attention:** Use the additional spray hose integrated in the cap for optimum dosage. Do not use on silicon compounds such as glass and stone. Treated surfaces are not paintable.

## TECHNICAL PROPERTIES

**Temperature resistance:** -50°C - +200°C

## TECHNICAL SPECIFICATIONS

**Chemical base:** Pure silicone oil in solvent

**Colour:** Transparent

## STORAGE CONDITIONS

A minimum of 36 months. Close the container properly and store in a dry, cool and frost-free location.

## PRODUCT DESCRIPTION

Universal transparent slipping, lubricating and anti-adhesion agent based on pure silicone oil.

## FIELD OF APPLICATION

For clean and light lubrication of sliding doors, sliding windows, drawers and bay windows, locks, wiring, cables, hinges, latches, zips, (curtain) rails, roller bearings, wheels and levelling feet, among others. Also for maintenance of (motor) bikes, scooters, machinery, (garden) tools and sports equipment.

Prevents dirt and grease deposits on biological waste bins, exhaust hoods, fans, ovens, microwaves, bumpers and grills. Makes cleaned textiles and leather water repellent, prevents freezing of (door) rubbers and keeps chains and gears clean.

## PROPERTIES

- Rust and corrosion resistant
- Water displacing
- Water repellent
- Electrically insulative
- Chemical resistant
- Low surface tension
- With extra precision spray hose
- Can be used in all positions

## PREPARATION

**Preliminary surface treatment:** Make sure that the surface is clean, dry, and free of grease.